

MILDEW RESISTANT COATING CONTROL II

CONTROL II is a Carbamate formulation that combined with a polymeric compound, forms a thin clear film that resists organic material growth, mold and mildew on hard and soft surfaces, including fabrics, walls and furniture. Can be used inside air conditioner ducts and can be added to acrylic and other water based paints. Apply with spray bottle, polysprayer, brush or rolled on clean surface to be treated, allowing sufficient time to dry. Do not rinse. Avoid contact with eyes. Refer to the label and attached SDS for additional instructions and The information precautions. contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron 3911 SW 47th AVE Davie, Florida 33314 Tel: (954) 584 - 4530 Fax: (954) 584 - 4531 www.chemtron.com PROFESSIONAL ENGINEERING PRODUCTS

 Acrylic polymer carrier with an active Carbamate additive
A ats as a long lasting surface

• Acts as a long lasting surface protecting coating

• Does not affect painted surfaces

• Flexible film formation

• Fast drying

• Water based with no strong odor

Appearance:Milky white liquid with no
particular odorBoiling point:100 °CSpecific gravity:1.01 gr/ccNon volatiles:2-5 %Solubility in water:TotalChemical type:CarbamateStorage stability:Keep away from directsun light and Acid productspH of liquid:Bestore8-9Flammability:Non-flammable

Packaging: 4 x 1 gallon Case 12 Qt. Case 5 gallon Pails

> Properties are typical and subject to usual manufacturing tolerances.

DERTIES