

**ANTIFREEZE SOLUTION****COOLANT ANTIFREEZE 50/50****FEATURES**

- Glycol solvents / Inorganic salts blend
- Works great in extreme cold and warm climate conditions
- Provides protection against rust
- Can be used on a variety of metal alloys
- Biodegradable

**PROPERTIES**

**Appearance:** Fluorescent Green liquid with no particular odor.

**Boiling point:** 230 °F

**Specific gravity:** 1.04 gr/cc

**Non volatiles:** 50 %

**Solubility in water:** Soluble

**Flash point:** None

**Storage stability:** Keep away from direct sun light and open flames

**pH of liquid:** 11-12

**Flammability:** Non-flammable

**Packaging:** 4x1 gallon Case  
55 gallon Drum

- Properties are typical and subject to usual manufacturing tolerances.

COOLANT ANTIFREEZE 50/50 is an antifreeze, coolant, antirust, anti-scale solution formulated for direct use in very cold and also warm climate conditions. It contains a special blend of antirust and antifreeze agents that enhance the performance of refrigeration systems and radiators and prevent re-deposition in the loop system.

COOLANT ANTIFREEZE 50/50 can be used for different metal alloys, including iron, soft steel and aluminum. It also protects brass and copper. It works in warm conditions to efficiently cool the water in the refrigerating system and in extreme hot engine conditions. Green fluorescent dye allows leaks in the refrigeration system to be detected easily.

COOLANT ANTIFREEZE 50/50 can be used in cars, trucks, busses, lorries and other refrigeration systems. It is ready to use, but can be diluted with water for warmer weather conditions. The dilution should not exceed 50 % water; and for better results, use de-mineralized or filtered water. Before using product, clean cooling system if the radiator and coil contain excessive mineral deposits. Refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron

3911 SW 47th AVE

Davie, Florida 33314

Tel: (954) 584 - 4530

Fax: (954) 584 - 4531

[www.chemtron.com](http://www.chemtron.com)

