

PROTECTIVE COATING

POLYBAR MS

FEATURES

- Seals metal surfaces and leaves a protective barrier
- Acrylic copolymer and wax coating system
- Neutralizes rust and inhibits corrosion up to six months
- Excellent adhesion to metal
- Safe to handle, water base emulsions
- Can be applied over painted surfaces

PROPERTIES

Appearance: Milky white emulsion with slight resin odor.

Boiling point: 212 °F

Specific gravity: 1.02-1.05 gr/cc

Non volatiles: 15-25 %

Solubility in water: Soluble

Flash point: None

Storage stability: Keep away from open flames and oxidizers

pH of liquid: 9-10

Flammability: Non-Flammable

Packaging: 5 gallon Pail
55 gallon Drum

- Properties are typical and subject to usual manufacturing tolerances.

POLYBAR MS is a polymeric coating formulated with acrylic copolymers, wax emulsions and antirust additives to neutralize rust activity on metals and protect metal surfaces from corrosion. It dries fast and will not affect the natural appearance of the surface. POLYBAR MS is a metal sealer and protector that can be used as a temporary coating for most metal parts, pipes, trucks, boats and tools. POLYBAR MS will not affect the surface and can be removed by a normal stripping.

Before applying product, clean the target surface. POLYBAR MS can be sprayed undiluted directly on the metal surface or by dipping into solution. It can also be applied by brush or sponge. If required, several coats can be applied. Leave sufficient time to dry before recoating. Do not mix POLYBAR MS with any other chemical. Refer to the label and SDS for additional instructions and precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron
3911 SW 47th AVE
Davie, Florida 33314
Tel: (954) 584 - 4530
Fax: (954) 584 - 4531
www.chemtron.com

