

GREASES

RED DOT GREASE

FEATURES

- All-purpose non-melt grease
- Extra “cushioning” that reduces shock and noise
- Superior acid and rust resistance
- Excellent load carrying capacity 65 lb Timken load
- Withstands temperatures up to 550 °F
- Exceptional adhesive-cohesive and anti-wear properties
- Seals out dirt contaminants
- Contains corrosion and oxidation inhibitors

PROPERTIES

Appearance: Red thick paste with characteristic grease odor

Water resistance: Excellent

***NLGI Grade:** 2

Penetration (ASTM D-217): 300-340 mm

Storage: Keep away from open flame and sparks.

Dropping point (ASTM D556): +550 °F (non-melt)

Flash point: > 400 °F COC

Solubility in water: Negligible

Timken OK Load (ASTM D-2509): 65 LB

Packaging: - Case of 24 or 48 x 14 oz tubes
- 45 or 120 lb pails

*National Lubricating Grease Institute

- Properties are typical and subject to usual manufacturing tolerances.

Red Dot Grease is an all-purpose non-melting grease, fortified with extreme pressure and anti-wear additives to provide heavy duty service. These special additive package allows our **Red Dot Grease** to resist extreme working conditions as well as weathering and chemical attack. **Red Dot Grease** also inhibits rust, corrosion and oxidation processes and resists heat well above working temperatures. These characteristics make this grease special for outdoor use, providing extra protection of equipment. This makes **Red Dot Grease** a true long lasting product that can replace many commercially available greases. Use as conventional greases. Do not ingest. Refer to the attached SDS for additional precautions. The information contained in this safety sheet is aimed at creating a guide for the selection and use of the product. However, we are not responsible for any use not recommended by ChemTron.

ChemTron
3911 SW 47th AVE
Davie, Florida 33314
Tel: (954) 584 - 4530
Fax: (954) 584 - 4531
www.chemtron.com

